

# SpotOn®

Model: PT-DIGITAL

## Spray Tip Pressure Tester



**Reads**  
**3-160 PSI**  
(0.2-11 Bar)

**Digital  
Test  
Gauge**

• Verify sprayer's pressure sensor or gauge  
• Find blockages in hoses and booms

**± 2%**  
**ACCURACY**

### Features:

- Installs between nozzle and nozzle body with industry standard quick connects. (Hardi requires adaptor)
- Includes battery with 5 year life
- For test gauge use only NOT for continuous use

Range & Units	Resolution	Accuracy
3.0 - 160.0 PSI	.5 PSI	± 2% or ± 1 PSI
0.20 - 11.00 Bar	0.05 Bar	± 2% or ± .07 Bar
20 - 1100 kPa	5 kPa	± 2% or ± 7 kPa

**1 YEAR WARRANTY:** This product is warranted to be free from defects in materials or workmanship for one (1) year from the date of purchase.

### innoquest inc.

910 Hobe Road  
Woodstock, IL 60098 USA  
815-337-8555 • www.innoquestinc.com

Assembled in USA with  
China and US parts

Innoquest Item #28040



© 2013 Innoquest Inc. USA P/N 28050 Rev. 0

### Gauge Operation




LCD Shows Pressure & Unit of Measure

Press ON button to turn gauge on. NOTE gauge **MUST** be turned on before applying pressure because it captures zero pressure at power on. The gauge turns off automatically if no pressure is applied within 15 seconds. The only way to turn the unit OFF is to wait 15 seconds for auto-off feature.

**Changing Pressure Units:** While the gauge is on hold the ON button until the display start flashing. Then while the display is flashing press and release the ON button to select the desired unit of measure. Once selected wait until flashing stops to use gauge.

### Battery Replacement

Approx. Battery Life is 5 Years so the need for battery replacement should be very limited (Depends on usage)



1. Remove protective rubber boot.
2. Remove both screws in back of case.
3. Remove and save sealing tape around outside of case.



4. Separate case to expose battery.
5. Slide battery out and replace with new CR2032 3 volt Lithium Coin Cell