

SpotOn®

SPRAYER CALIBRATOR



ACCURATE FLOW RATE MEASUREMENT IN SECONDS

SPRAYER CALIBRATOR SC-1 SPECS:

Best for flow rates below 1 GPM typical of herbicide and insecticide application

Range & Units: 0.02 – 1.00 GPM
(0.08 – 3.80 L/Min)

Accuracy: +/- 2.5%

Size: 2.25”(5.7cm) Dia x 9.25”(23.5 cm) Tall

Weight: 0.52 lbs(236g)

SPRAYER CALIBRATOR SC-4 SPECS:

Best for higher flow rates between 1-4 GPM typical of liquid fertilizer application

Range & Units: 0.07 – 4.00 GPM
(0.27 – 15.0 L/Min)

Accuracy: +/- 4%

Size: 4”(10.2cm) Dia x 10”(25.4cm) Tall

Weight: 1.2 lbs(544g)

Every unit is hand calibrated and verified with water to assure top accuracy in the field.



FEATURES:

- **Quickly find worn spray nozzles tips**
Industry guidelines recommend tip replacement once flow rate exceeds that of a new tip by 10%
- **Accurately measure true tip flow rate**
Today's high tech sprayers can only be properly calibrated and confirmed with this knowledge
- **Fast and simple operation**
Readings in 10 seconds or less per tip
- **Displays in GPM, Liters/min or oz/min**
- **JKI - Julius Kuhn-Institut Certified G 2050**

Featured in the Journal of Pesticide Safety Education
The SpotOn® Sprayer Calibrator, a Digital Flow Meter: Accuracy Evaluation and Use in Pesticide Safety Education Programs



YOUTUBE.COM
SEE THE DEMO VIDEO. SEARCH:
SpotOn Sprayer Calibrator

SC-1 ■ Item #: 23890 ■ List Price: \$155.00 USD ■ One year warranty

SC-4 ■ Item #: 24200 ■ List Price: \$226.00 USD ■ One year warranty